

VANLIGSTE LAGERFØRTE DIMENSJONER:

Utv. diameter	Gods	Utv. tommer	Pund/fot	Kg per meter
114.3 mm	7.4 mm	4.1/2"	13.5 lb/ft	20,1
114.3 mm	8.5 mm	4.1/2"	15.1 lb/ft	22,5
139.7 mm	7.7 mm	5.1/2"	17.0 lb/ft	25,3
139.7 mm	9.2 mm	5.1/2"	20.0 lb/ft	29,8
177.8 mm	10.3 mm	7"	29.0 lb/ft	43,2
177.8 mm	11.5 mm	7"	32.0 lb/ft	47,6
244.5 mm	12.0 mm	9.5/8"	47.0 lb/ft	70,0
244.5 mm	13.8 mm	9.5/8"	53.5 lb/ft	79,6
273.0 mm	13.8 mm	10.3/4"	60.7 lb/ft	90,3
339.7 mm	12.2 mm	13.3/8"	68.0 lb/ft	101,2
339.7 mm	13.0 mm	13.3/8"	72.0 lb/ft	107,2

SPESIFIKASJONER STÅLGRADER FOR CASING:

Stålgrad	Flytegrense		Strekk
	Min. MPA	Maks MPA	
L-80	551 MPA	655 MPA	655 MPA
N-80	551 MPA	758 MPA	689 MPA
C-95	655 MPA	758 MPA	723 MPA
P-110	758 MPA	965 MPA	861 MPA